

AUDIO WAVE

Active 250

Output Power @ 14.4V @ 0.1% THD

1 x 8 Ohms - 160 Watt RMS

1 x 4 Ohms - 270 Watt RMS

1 x 2 Ohms - 390 Watt RMS

Output Power @ 16V @ 0.1% THD

1 x 8 Ohms - 200 Watt RMS

1 x 4 Ohms - 340 Watt RMS

1 x 2 Ohms - 450 Watt RMS

Two amps bridged @14.4V @ 0.1% THD

1 x 8 Ohms - 330 Watt RMS

1 x 4 Ohms - 540 Watt RMS

Two amps bridged @16V @ 0.1% THD

1 x 8 Ohms - 400 Watt RMS

1 x 4 Ohms - 680 Watt RMS

Bandwidth 9.5Hz - 120KHz (-2dB)

Sensitivity input 0.1V - 2V

Input impedance 33K

SNR A/WTD not less than -124dB at full power output

Input power 9 -16 Volts DC

Idle Current - +/- 1.3 Amps

Max current 60 Amps @ 2 ohms and 32 amps @ 4-ohm load

Chassis size 360mm x 152mm x 80mm

Weight 5.90 Kg

ADDITIONAL SPECIFICATION INFORMATION

SNR A/WTD @ 1Watt output

8 Ohm -106dB

4 Ohm -102dB

IMD 0.0043% 60Hz/7KHz

8/4/2 Ohm 0.0001THD+N @1 Watt

FIND OUT MORE

