

AUDIO WAVE

Aspire Pro MB CA V2

**Mono Amplifier 1 -8 Ohm Stable
Working Voltage 9 - 16VDC**

Minimum Output @14.4 Volts

**CA 8 Ohm - - 50 Watts RMS @ 0.0020% THD
A - - 55 W RMS @ 0.1% THD**

**CA 4 Ohm - - 30 Watts RMS @ 0.0020% THD
A/B - - 90W RMS @ 0.1% THD**

**CA 2 Ohm - - 10 Watts RMS @ 0.0030% THD
A/B - - 150W RMS @ 0.1% THD**

**CA 1 Ohm - - 2 Watts RMS @ 0.0050% THD
A/B - - 160W RMS @ 0.1% THD**

Signal to noise ratio A/W Full Power (Op Amp pass through) > -118dB

Signal to noise ratio A/W Full Power > -102dB

Frequency Response 12Hz-100KHz (-1db)

**Input impedance 33K Ohms
Input sensitivity (Op Amp bypass switch on) 0.1V - 1V
Input sensitivity 0.3V - 8V
Alps Gain control +15dB**

Phase Switch 0 - 180 Deg

Idle current + - 9 Amps

Thermal cut out (3 x internal variable speed fans) 80 degrees celsius

Internal fuse rating 2 x 15 Amps

DC protection cut off > 9.00Hz

Dimensions (H) 64mm x (W) 378mm x (D) 339mm

Weight 7.2kg

FIND OUT MORE

