

# AUDIO WAVE

# Aspire Pro

**Stereo Amplifier 4 - 8 Ohm stable**  
**Voltage input 8V - 16V**

**Minimum output at 4 Ohm loads @ 14.4 Volts**  
**2 x 100 w RMS @ - 0.01% THD**  
**2 x 240 W RMS @. - 0.1% THD**

**Minimum output at 8 Ohm loads @ 14.4 Volts**  
**2 x 100 W RMS @ - 0.01% THD**  
**2 x 160 W RMS @ - 0.1% THD**

**Bridge**  
**1 x 500 W RMS @ 8 Ohm - 0.1% THD**  
**1 x 540 W RMS @ 6 Ohm - 0.1% THD**

**Signal to noise ratio A/W - Full Power - >-105dB**

**Frequency response 12Hz-100KHz (-1dB)**

**Input impedance - 33K Ohms**

**Input sensitivity - 0.3V - 8V**

**Idle current - + -3.0 Amps**

**Thermal cut out - 80 Deg C**

**Internal fuse rating - 2 x 30 Amps**

**DC protection cut off - > 9.00 Hz**

**Dimensions**  
**(H) 64mm x (W) 378mm x (D) 339mm**

**Weight**  
**7.6kg**

**Available in Black or White chassis**

**Available in Black, White, Gold, UJ Flag or US Flag PCB's**

**FIND OUT MORE**

