

# **AUDIO WAVE**

# **Excel Direct Input**

**Stereo amplifier 2- 8 Ohm stable Bridged 4 – 8 Ohm stable**

**Minimum output at 8 Ohm loads @ 14.4 Volts  
2 x 45 W RMS @ 0.1% THD**

**Bridged at 8 Ohm loads  
1 x 200 W RMS @ 0.1% THD**

**Minimum output at 4 Ohm loads @ 14.4 Volts  
2 x 75 W RMS @ 0.1% THD**

**Bridged at 4 Ohm loads  
1 x 300 W RMS @ 0.1% THD**

**Minimum output at 2 Ohm loads @ 14.4 Volts  
2 x 110 W RMS @ 0.1% THD**

**Signal to noise ratio A/W Full Power > - 99dB**

**Frequency response 10 Hz-100KHz (-2dB)**

**Input impedance 15K Ohms**

**Input sensitivity 0.1V – 2V**

**Idle current + - 1.0 Amp**

**Input power voltage 9V-16VDC**

**Internal fuse rating 1 X 30 Amp**

**Dimensions Excel**

**H) 64mm x (W) 309mm x (D) 226mm\  
Weight 4.6kg**

**Dimensions Excel DST**

**(H) 64mm x (W) 580mm x (D) 226mm  
Weight 8.4kg**

**Dimensions Excel TST**

**(H) 64mm x (W) 850mm x (D) 226mm  
Weight 10.3kg**

**FIND OUT MORE**

